CAMEX LIMITED
REGD. OFF. : CAMEX HOUSE, 2ND FLOOR, STADIUM - COMMERCE ROAD, NAVRANGPURA, AHMEDABAD - 380 009
PH. : 66307200, 26462260, 26462262 FAX : 91-079-26462123
WEB : camexcolours.com E-MAIL : camex@icenet.net

CAMAWHITE KSF

READY KHADI PASTE FOR PRINTING

SALIENT FEATURES

- ► Excellent crock & wash fast prints
- ► Non – chocking
- ► Enables to produce sharp & fine line prints
- ► High resistance to mechanical shear
- ► Prints are smooth, soft & elastic

CHARACTERISTICS

Appearance	: Thick white paste
Chemical Nature	: Inorganic product based on Titanium dioxide
Ionic Nature	: Nonionic
Miscibility	: Easily miscible with water in all proportions
pH	: 7 ± 0.5
Compatibility	: Excellent with hard water, inorganic & organic pigments

APPLICATION

Substrate	: Cellulosic fabric & its blends with polyester
Machines	: Printing equipments & machines
Function	: Ready khadi paste for printing
Guide Recipes	:

- ***Preparation of Print Paste –***

CAMAWHITE KSF	**93**	**parts**
Catalyst DAP	**3**	**parts**
CAMAFIX CCL	**2**	**parts**
Ammonia (25%)	**2**	**parts**

Bulk to	**100**	**parts**

- Print – Dry – Cure at 150° C for about 4 – 6 minutes.

SPECIAL REMARKS

Storage Stability	: Minimum 6 months under normal conditions of storage
Container	: 50 & 200 kg Carbuoys & barrels

Disclaimer: All recommendations for the use of our products, whether given by us in writing, orally or to be implied from the results of trials, are based on our present state of knowledge & experience. Owing to the variation in local application conditions, they can not be claimed to be complete. Hence, we can not accept any responsibility thereof. All claims, liabilities – also with a view to claim of third parties – are excluded. It is advised to conduct lab & bulk trials before using in bulk production.